



Mexapol®

High solids floor polish

- Very durable metallised emulsion floor polish.
- Dries to a slip resistant high gloss finish.
- Excellent levelling properties for easy application and to ensure a smooth even finish.
- Very scuff resistant to make it easier to clean & maintain.
- Responds to high & ultra high speed burnishing.
- Suitable for most hard floors including vinyl, rubber, linoleum, terrazzo & sealed surfaces.
- Ideal for heavy traffic areas.
- Coverage per 5lt - 400/500 sq. mtr for 1 coat.
- Pack size: 2 x 5 litre. Order code: A074EEV2



HOW TO USE

Ensure floor is clean, dry & neutral.

Use undiluted.

Pour polish into clean bucket or tray, alternatively pour directly onto the floor in a thin line.

Place clean mop or applicator into polish and spread thinly and evenly in WEST to EAST direction.

Leave to dry for approximately 30 minutes.

Apply a further coat of polish thinly & evenly at right angles to first i.e. NORTH to SOUTH. Leave a 10cm gap at the floor edge to avoid a build up.

Leave to dry for approximately 30 minutes.

A third coat may be required in heavy traffic areas or on old or worn floors.

**For more detailed information please refer to
EVANS GUIDE TO FLOOR CARE &
EVANS TRAINING SUPPORT DVD**

PRODUCT INFORMATION:

Appearance:	Opaque white liquid
Odour:	Characteristic
pH - undiluted:	8.5
Shelf life:	Not less than 3 years

COMPOSITION:

Contains an aqueous dispersion of metallised acrylic co-polymers, wax emulsion, plasticisers, coalescent, defoamer, levelling agent & preservative.

BIODEGRADABILITY:

All surfactants used in Evans Vanodine products comply with the current European Regulations concerning biodegradability and protection of the environment.

QUALITY ASSURANCE:

This product is manufactured in the U.K. by EVANS VANODINE INTERNATIONAL PLC under an ISO 9001 Quality Management System Cert. No. FM 09535 and an ISO 14001 Environmental System Cert. No. EMS 506072 registered by the British Standards Institution.

Distributed by:

REVISION DATE:21/10/10

Visit our
website

